



15575 N. 83RD Way, Ste. A1, Scottsdale, AZ 85260
 Tel. 480.998.3033 | Fax: 480.998.3055 | email: contact@polylastsystems.com

MATERIAL SAFETY DATA SHEET

MATERIALS (CAS)	WT%	OSHA PEL	(ACGIHTLV)
Vulcanized Rubber Compound	Approx. 99%	N/A	N/A
Talc (Hydrous Magnesium Silicate)	Less than 4%	2.0 mg/m3	2.0 mg/m3
FLASH POINT: Ignition temperature of dust cloud 320 degrees Centigrade (608 F) approximately		FLAMMABLE LIMITS	N/A

HAZARDOUS INGREDIENTS

PRODUCT IDENTIFICATION/CHEMICAL & PHYSICAL CHARACTERISTICS

PRODUCT NAME	Crumb Rubber	SOLUBILITY IN WATER	Insoluble
APPEARANCE	Black granular powder	ODOR	Slight smell of vulcanized rubber
SPECIFIC GRAVITY	Less than 4%	MELTING POINT	N/A
VAPOR PRESSURE	N/A	VAPOR DENSITY	N/A
EVAPORATION RATE	N/A	BOILING POINT	N/A